
 **Smart Switch Module**
智能隱藏控制器

 **Smart Dimmer Switch**
智能光暗掣

 **Smart Curtain Kit**
智能窗簾電機套裝

 **Smart Light Switch**
智能燈掣


 **Smart Bulb Adapter**
智能燈頭轉換器

 **Smart Roller Kit**
智能捲簾電機套裝

 **Smart Universal Remote**
智能通用遙控器

 **Smart Outlet**
智能插座

 **Smart Furniture**
智能家具

 **Smart Plug**
智能轉換插蘇



No Hub
免設置網關



No Rewiring
免重新鋪線



No Setup
免首次設定



No Pairing
免手動配對

OUR SMART HOME SOLUTION FOCUS ON SIMPLICITY AND FUNCTIONALITY

簡單、實用、功能齊全的智能家居方案



 **Mobile As***
Hub
網絡控制


 **Voice***
Control
語音控制

 **Mesh-like**
Network
設備組網

 **Remote***
Control
遙控功能

 **Rooms and**
Scenes
場景模式

 **Away***
Detection
離開感應

 **Schedule**
Timers
定時開關

 **Password**
Protection
密碼保護

IF
IF This
Then That

* This function works only when the app is switched on. In addition, the performance may be subjected to many factors, including but not limited to server stability, Bluetooth chips and OS version. Yoswit will keep updating the mobile application in order to improve the performance and stability.

The product can be operated on smart phones in iOS 7.0 or Android 4.3 with Yoswit app installed. In addition, the smart phone must be in Bluetooth Smart Ready.

+ The connection speed and performance may be subjected to many factors, including but not limited to distance, Bluetooth chips and OS version.

x The range of a Bluetooth connection is typically given as about 3-20m.

x The rating is for purely resistive load. The maximum load will be vary from different load type. For details, please refer to the specification in the user manual.

* 此功能需配合手機應用程式於長期開啟下使用，其表現有機會受伺服器網絡穩定性和應用程式系統更新等因素影響。Yoswit將透過應用程式更新提升相關功能的效能及穩定性。

本產品支援iOS 7.0或Android 4.0以上版本之智能設備，同時藍牙版本必須為Bluetooth Smart Ready或 Bluetooth Low Energy或其以上之版本。

+ 受限於不同的手機部件及系統版本，藍牙連接速度將會有所不同。

- Yoswit智能產品與控制器（手機或平板）的室連接距離為3-20米。並會因應牆身厚度，轉角位及控制器的藍牙收發強度而有所不同。

x 此參數只適用於阻性負載類型的產品。連接不同類型的產品最高負載將有所不同，詳情請參考產品說明書。

PRODUCT CATALOG 產品目錄

Smart Electrical Switch 智能電器開關



YO815 YO825



YO835 YO845

Smart Light Switch - Socket 86 智能燈掣- 86型開關面板



Support both 2-wire and 3-wire installation
兼容單火及零火接線 ◆

Max Load Current 最大負載: 6A★



YO815c

Smart Double Pole Switch - Socket 86 智能曲架掣- 86型開關面板



Work well with AC, Heater and Ventilation Fan
兼容冷氣機, 熱水爐及抽氣扇

Max Load Current 最大負載: 20A / 2HP★



YO825m YO845m

Smart 3-way Switch - Socket 86 智能雙路掣- 86型開關面板



Support both 2-wire and 3-wire installation
兼容單火及零火接線 ◆

Max Load Current 最大負載: 6A★



YO825k YO845k

Smart Curtain / Roller Switch - Socket 86 智能窗簾/捲簾掣- 86型開關面板



Customizable run time of the motor
自定義電機運行時間及距離

Max Load Current 最大負載: 6A / 400W★



YO515uk

Smart Outlet (UK) 智能插座 (英規)



Built-in power consumption feature
內置計電功能

Max Load Current 最大負載: 13A★



YO619d / YO619v /
YO619

Smart Switch Module 智能隱藏控制器



Applicable to lights and motors
適用於燈具及電機

Options 選項: On/Off, TRIAC, 0/1-10v

Max Load 最大負載: 10A (On/Off), 400W (TRIAC)★
100MA / 50 Bulbs (0/1-10v)

Smart Dimming Solution 智能調光方案



YO815d ●

Smart Dimmer Switch - Socket 86 智能光暗掣- 86型開關面板



Support both TRIAC and 0-10V Dimming
支援可控矽及0-10V調光

Max Load Power 最大負載 (TRIAC): 400W★

Max Load Current (0/1-10v): 100MA / 50 Bulbs
最大負載



YO680XX

Dimming LED Driver (TRIAC / 0-10v) 調光電源 (可控矽 / 0-10v)



Varies options for different bulbs
多款型號適合不同功率電泡

Option 選項: 5w~200w

0-10v C.C Driver / 0-10v C.V Driver / TRIAC C.C Driver /
TRIAC C.V Driver / TRIAC C.V Driver PWM output

Automatic Shading 電機組合



YS125

Smart Curtain 1 Layer / 2 Layers 智能單層窗簾 / 雙層窗簾組合



Customizable track length and track shape
可按窗台形狀度身訂做路軌

Track Length (m) 窗簾路軌長度 (米): ≤12



YS145

Smart Blinds 智能捲簾組合



YS225

Applicable to blinds and projector screen
適用於捲簾及投影幕

Tube Length (m) 傳動管長度 (米): ≤12

Plug & Play 即插即用



YO101i

Smart Universal Remote 智能通用遙控器



Customizable shortcut keys
自定義控制按鈕

Power Supply : 3A Battery / USB
供電方法



YO919 ■

Smart Bulb Adapter 智能燈頭轉換器



Convertible among E14,
E27 and B22
可轉換E14, E27, B22燈頭

Max Load: 60w
最大負載



YO602uk ■

Smart Plug (UK) 智能轉換插蘇 (英規)



Applicable to lights, fans,
boilers, etc
適用於燈具, 風扇, 水壺, 等等

Max Load Current: 10A★
最大負載

★ The rating is for purely resistive load. The maximum load will be vary from different load type. For details, please refer to the specification in the user manual.

- ◆ The product supports both 2-wire and 3-wire installation. If 2-wire is in use with low power LED bulb or non-reputable brands, the support is limited. When you encountered conditions of circuit instability, lightings gleaming or no light, please refer to the recommended solutions in user manual.
- The Smart Bulb Adapter and Smart Plug is now using Bluetooth 4.0 which it cannot support mesh-like network or simultaneous connection with different users.
- The switch cannot guarantee to support all dimming products in the market, please refer to our product page with all tested bulb models or conduct the test of your lamp before choosing the product.

★ 此參數只適用於阻性負載類型的產品。連接不同類型的產品最高負載將有所不同, 詳情請參考產品說明書。

- ◆ 本產品同時適用於零火及單火佈線, 但於單火接線時有機會不能支援部份低功率或非主流品牌的LED燈泡。假如出現不能起動或閃爍的現象, 請參考產品說明書了解有關詳情及解決方法。
- 智能燈頭轉換器及智能轉換插蘇暫不支援設備組網功能。
- 調光開關不確保兼容市面上所有的調光燈具, 建議購買前諮詢技工評估或安排樣品測試。已經測試的燈具清單會不斷更新, 並刊登於產品專頁上。